


FICHA TÉCNICA

K LIGHT
By Kratos Safety

SLU041

NEWTON 2
HL 10 101 00

HS Code : 85131000
Barcode : 3700671407784



	Brightness	Running Time
Focused 100%	400 lumens	4 hours
Focused 5%	20 lumens	60 hours
Flood 100%	200 lumens	7 hours
Flood 5%	20 lumens	60 hours
Red light 100%	20 lumens	10 hours
Red light 25%	5 lumens	80 hours

Dimensions

69 x 46 x 39 mm / Printed box : 171 x 109 x 50 mm

Safety

Directive **2014/30/UE**
2001/95/UE
2011/65/UE
2012/19/UE



LED Risk(c) : Group 1 - Risk limited by normal behavioural limitations. Measures under NF EN 62471 Standard.

Assets

- Many different lighting modes (flood, focused, red).
- SOS feature available in every lighting mode.
- Progressive dimmer available on every lighting mode with memorization of the last setting.
- Wide light beam (up to 110°).
- IP65: Excellent water and dust resistance.
- Easy to use: Only two buttons.

Use

Flood for working near feet area; **Flood Red** for night vision or close-in work application; **Focused** for work within easy reach. **SOS mode** available on all 3 modes.

Stepless dimmer on all 3 Lighting modes with memorization of the last setting.

Indication of remaining capacity in the battery <20% the light will blink 3 times.

Temperatures: -10°C / +40°C.

Application : Industry, Construction, Maintenance, roadworks, Networks & Work at height (also suitable for leisure, climbing and outdoor activities).