


FICHA TÉCNICA

VSG323K



FA 60 007 00



HS CODE
6307909899
CARTON SIZE / PCS.
60 x 40 x 24 cm / 5
AET (UE) N°2777/13781-01/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland







Frimsal Distribuciones, S.L.




Avda. Canaletes, 45 - 08290 Cerdanyola (Barcelona)

C/ Repostería, 7 - Pgno. Ind. San Rafael - 41620 Marchena (Sevilla)

Telf. 902 125 661 - Fax. 902 102 156 - E-Mail; info@frimsal.es

<http://www.frimsal.com>

REF.	FA 60 007 00
CE	PPE regulation (EU) 2016/425 Annex II using EN 795:2012, TS 16415:2013
	x2
MAT.	 30 mm PES
R (kN) / MBS (kN)	19 kN / 23 kN
MAT.  	
LG. / f MIN. → MAX.	5.0 m → 20.0 m / 0.8 m → 3.2 m
	3.43 KG

	R (kN) / MBS (kN)
Nombre d'utilisateurs Number of users Cantidad de usuarios Cantidad de usuarios Quantità di utilizzatori Quantità di utilizzatori Anzahl der Benutzer	Résistance statique (en kN) / Résistance à la rupture Static strength / Minimum Breaking Strength Resistencia estática (en kN) / Resistencia a la ruptura (en kN) Resistencia estática (in kN) / Resistencia a la ruptura (in kN) Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)
MAT.  	LG. / f MIN. MAX.
Matière connecteur / tendeur Material of connector / tensioner Material del conector / tensor Material del conector / tenditore Material Verbinder / Spanner	Longueur mini → maxi / Flèche mini → maxi Min. → Max. length / Min. → Max. deflection Longitud mínima → máxima / Flecha mínima → máxima Lunghezza min. → max. / Flessione min. → max. Länge min. → max. / Dirchhang min. → max.